

# 1981-87 Toyota Pickup Buckets Installation



## Step 1. Driver & Passenger Bottom/DB&PB:

All the parts of your seat cover are labeled on the inside right corner. Use the seat cover part ID chart to ID parts. Place the bottom covers on with the extending hook Velcro™ to the front. Line up the seams of the seat cover to the seams on the seat, they should match closely.



## Step 2. Driver & Passenger Bottom/DB&PB:

Tuck the back edge of the seat cover in and pull back hard



## Step 3. Driver & Passenger Bottom/DB&PB:

Form the right and left rear corners of the seat cover over the seat. Route the long Velcro™ under the front of the seat, and tuck the side Velcro™ between the seat and the plastic cowling, over the seat slides. Again, line up the seams of the seat cover to the seams of the seat.



## Step 4. Driver & Passenger Bottom/DB&PB:

Use one hand in a smoothing action from front to back on top of the seat cover while pulling the long front Velcro™ tight, pressing them to the loop Velcro™ sewn on the back edge as shown. Connect the two side to side Velcro™ at an angle, and like the front Velcro™ by sweeping your hand down the side of the seat cover from front to back while pulling on the Velcro™ to tighten it up, then connect them to the loop Velcro™ sewn on back as shown. Snap the plastic buckles over the seat support wire as shown, then back to the rear loop Velcro™. Trim the excess Velcro™.



**Step 5. Driver & Passenger Bottom/DB&PB:**

Remove the snap buckle from the Velcro™. Route the Velcro™ between the frame as shown. Clip the buckle where shown in the hole of the seat metal pan, then run the Velcro™ through it, tighten, then press the Velcro™ together, trim the excess.



**Step 6. Driver & Passenger Top/DT&PT:**

Remove the headrests by reclining the seat (if they are in the truck) gently lift up and depress the push button release until they come out. Slide the seat covers on with the extending hook Velcro™ to the front seen in Step 7. Carefully tuck the seat cover under the plastic for the headrests, starting with the push button side.



**Step 7. Driver & Passenger Top/DT&PT:**

Again, line up the seams of the seat cover to the seams of the seat, they should match closely. Tuck the Velcro™ into the seat and tip the seat forward



**Step 8. Driver & Passenger Top/DT&PT:**

Use one hand in a smoothing action down the front of the seat cover while gently pulling on the Velcro™ from the back. Use the front hand to hold the Velcro™ tight to the seat (shown) pinning it in place, then press the loop Velcro™ to it with the other hand.



**Step 9. Headrests/H:**

Slide the covers on with the extending Velcro™ to the front.



**Step 10. Headrests/H:**

Tuck the hook Velcro™ under the back edge and connect it to the loop Velcro™ sewn inside the back.