

1995-1999 Suburban 3rd Row Bench Installation



Step 1.
Seat removal is difficult and should be unnecessary to install the covers. Using a short Phillips screwdriver remove the seat strap and set it aside. then, temporarily remove the headrests by depressing both push button releases while gently lifting up.



Step 2. Top/T:
All the parts of the seat cover are labeled inside. Use the seat cover piece identification chart to ID parts. Slide the cover on with the extending hook (sticky) Velcro™ to the front.



Step 3. Top/T:
Tuck the fabric under the plastic for the headrests, starting with the pushbutton sides first.



Step 4. Top/T:
Work the fabric inside the on the top corners from thumb to forefinger.



Step 5. Top/T:
Work the fabric inside the seat cover around the back corners from thumb to fore finger.



Step 6. Top/T:
Tuck the front edge of the seat cover in.



Step 7. Top/T:

Use one hand in a smoothing action down the front of the cover from top to bottom while pulling on the Velcro™ from behind, then press the hook Velcro™ onto the carpet on the back side of the seat. Work from one side to the other.



Step 8. Top/T:

Next, pull the side Velcro™ and press it onto the seat carpet.



Step 9. Top/T:

Press the side hook Velcro™ onto the seat carpet, covering up the side Velcro™.



Step 10. Top/T:

Lastly, pull the back edge down and press the hook Velcro™ onto the carpet moving from one side to the other.



Step 11. Top/T:

Put the seat strap back on using the provided hole in the cover.



Step 12. Bottom/B:

Place the cover on with the long hook Velcro™ to the front.



Step 13. Bottom/B:
Notice the Velcro™ in the seatbelt area.



Step 14. Bottom/B:
Tuck the seatbelt area into the seat bottom.



Step 15. Bottom/B:
Pull the cover around the back left and right corners.



Step 16. Bottom/B:
Tuck the back edge in.



Step 17. Bottom/B:
Pull the cover back and around the back corners.




Step 18. Bottom/B:
Tuck the cover behind the seat release plastic.



Step 19. Bottom/B:
Route the shortest hook Velcro™ from the front to the loop (fuzzy) Velcro™ that's on the front of the seatbelt opening.



Step 20. Bottom/B:
Route the left and right seatbelt Velcro™ at an angle to the loop Velcro™ that's sewn on the back edge of the cover.



Step 21. Bottom/B:
Route the long left and right side Velcro™ at an angle and press it onto the rear loop Velcro™ at an angle.



Step 22. Bottom/B:
Clip the three plastic Velcro™ buckles where shown, over the metal bar, then press it onto the rear loop Velcro™ on the left, middle and right passenger areas.



Step 23. Bottom/B:
Route the remaining Velcro™ as shown to the rear loop Velcro™, note the locations of the plastic buckles.



Step 24. Headrests/H:
Slide the covers on with the extending hook Velcro™ to the front.



Step 25. Headrests/H:
Work the fabric inside the cover to the back.



Step 26. Headrests/H:
Lastly, tuck the fabric under the back edge and press the Velcro™ together.