

# 1995-2000 Tacoma Regular Cab 4X4 Bench Seat Installation



**Step 1.**  
Both parts of the seat cover are labeled inside.  
"T" is for top, and "B" is for the bottom.  
Place the top on with the extending hook Velcro™ to the front.



**Step 2. Top/T**  
Pull the cover down and form it to the integral headrests.



**Step 3. Top/T**  
Manipulate the seam fabric inside the seat cover from thumb & middle finger to pointer the finger.



**Step 4. Top/T**  
Tuck the hook Velcro™ into the seat, routing them under the bar. Use one hand in a smoothing action down the front of the seat from top to bottom, while gently pulling on the Velcro™ with the other hand from behind. Pin it to the seat with the front hand and press the Velcro™ together. Work from one side to the other.



**Step 5. Bottom/B**  
Feed the seat belts through the provided openings.



**Step 6. Bottom/B**  
Work the fabric inside the seat cover seam outward, or from thumb to forefinger.





**Step 7. Bottom/B**  
Tuck the back edge in.



**Step 8. Bottom/B**  
Route the hook Velcro™ between the seat slide and the seat, just in front of the hinge arm.



**Step 9. Bottom/B**  
Route the rear most side hook Velcro™ behind the hinge arm and route it around the back corner.



**Step 10. Bottom/B**  
Mate both side hook Velcro™ to the loop Velcro™ sewn on the back edge at roughly a 45 degree angle.



**Step 11. Bottom/B**  
Slide the seat all the way forward and route the long front hook Velcro™ under the seat. Mate them to the loop Velcro™ on back. The two center Velcro™ route easiest along the transmission hump.



**Step 12. Bottom/B**  
Connect the three plastic buckles under the back edge of the seat. One in the middle, one for passenger, and one for the driver side. See step 15 for view.



**Step 15. Bottom/B**  
View of rear buckle.



**Step 16. Bottom/B**  
Fasten the side buckle to the 3" wide metal frame,  
then back to itself. Trim excess if necessary.