

1995-98 Ford Bench w/ Integral headrests Installation



Step 1. Top/T:

Slide the seat cover on with the extending hook (sticky) Velcro™ to the front. Line up the seams of the seat cover up to the seams of the seat, they should closely match.



Step 2. Top/T:

Next, manipulate the fabric from the seams inside the seat cover to the center, from thumb to forefinger on the top of the seat. This will provide a wrinkle free fit.



Step 3. Top/T:

Manipulate the fabric on the left and right side cap outward, from thumb to forefinger.



Step 4. Top/T:

Fold the backrest forward; tuck the fabric and Velcro™ between the seat and the metal bar. Press the hook Velcro™ to the loop Velcro™ together.



Step 5. Bottom/B:

Place the seat cover on with the long hook Velcro™ to the front. Work the fabric around the front corners outward, from forefinger to thumb.

Some trucks have plastic drink holders in front. Slide them up and remove them temporarily. Next remove the metal studs for holding the drink holders with an Allen wrench and set them aside for Step 12.



Step 6. Bottom/B:

Tip the backrest ahead pull the rear left and right sides around the back corners, putting the metal piece through the provided hole.



Step 7. Bottom/B:

Line up the seams of the seat cover to the seams of the seat around the front and sides. Tuck the back edge of the seat cover in, lining up the seatbelt openings, but don't stick the Velcro™ it yet. Route the long hook Velcro™ under the front of the seat, between the seat and the seat slide wire.



Step 8. Bottom/B:

Mate the long hook Velcro™ to the carpet on the back edge of the seat



Step 9. Bottom/B:

Make sure the fabric is tucked behind the plastic arm on the sides of the seat. Carefully route the two rear most side hook Velcro™ around the metal bar as shown and mate them to the carpet on the back edge of the seat.



Step 10. Bottom/B:

Route the furthest forward side Velcro™ through the slot in the seat slide and mate it to the carpet on the back edge of the seat. Pull on the back edge of the seat cover, line up the slots for the seatbelts, and press the hook Velcro™ sewn inside the back edge to the carpet on the back edge of the seat.



Step 11 Bottom/B:

THIS PICTURE IS NOT FROM YOUR 1995-98 F-150.
Attach the plastic hook with Velcro to the metal plate pictured on step 12, then fasten it back to itself.



Step 12. Bottom/B:

The seat cover was updated with Velcro™ (no Ropes). The picture on Step 12 is to show you the underside of the seat, and the location of the metal plate. Probe for the holes for the drink holder studs with a pin. Cut a small "X" where the opening is. Don't worry, it won't unravel.

