

1999-2002 Chevy/GMC Extended Cab Rear Installation



Step 1. Top/T:

Lift the seat bottom up into the backrest and pull the headrests all the way up. While holding gentle upward pressure insert a heavy paper clip or piece of wire into the holes in the plastic until the headrests release.



Step 2. Top:

The pieces of your seat covers are labeled inside. Use the "Seat Cover Piece Identification Chart" to ID the pieces of the seat cover. With the seat bottom partway up, place the seat cover on with the long hook (sticky) Velcro™ to the top as shown.



Step 3. Top:

Tuck the fabric under the plastic for the headrests.



Step 4. Top:

Slide the long hook Velcro™ down behind the seat.



Step 5. Top:

Tuck the seat cover into the seat and route the long side hook Velcro™ (thumb) on the left and right, between the backrest and bottom, around to the side, and mate them to the loop Velcro™ sewn inside (pointer finger). This may take a few tries to get the best fit.



Step 6. Top:

Tilt the seat bottom all the way up and reach up from the bottom for the long hook Velcro™, connecting them to the loop Velcro™ sewn inside the bottom edge (shown). Slowly move the seat bottom up and down to make sure the seat's action is not being impeded. If so, adjust the Velcro™.



Step 7. Bottom/B:

Slide the seat cover on with the cut-out for the seat release straps to the bottom. Feed the straps through the provided openings



Step 8. Bottom:

Tuck the seat cover into the seat and mate the hook fasteners to the carpet on the back edge of the seat. Start on one side and work towards the other.



Step 9. Bottom:

Similar to step 8, mate the Velcro™ to the carpet on the bottom of the seat.



Step 10. Headrests/H:

Slide the covers on with the hook Velcro™ to the front. Mate them to the loop Velcro™ sewn in back.