

# 1999-2004 Dakota Crew Cab Rear 40-60 Installation



**Step 1. Prepare the seat for Installation:**  
Temporarily slide the seat belts out of the elastic.  
All parts of the seat cover are labeled on the inside right of each part. Use the Seat Cover Part ID Chart.



**Step 2. DT&PT/Driver & Passenger Top:**  
Form the top of the seat cover to the top of the seat, lining up the seams of the seat cover to the seams on the seat, they should match closely.



**Step 3. DT&PT/Driver & Passenger Top:**  
Press the hook Velcro™ onto the carpet that's on the backside of the seat.



**Step 4. DT&PT/Driver & Passenger Top:**  
Tuck the front edge of the cover in, along with the two hook Velcro™ sewn on the front edge.



**Step 5. DT&PT/Driver & Passenger Top:**  
Lift the seat bottoms up, feed the two Velcro™ thru.



**Step 6. DT&PT/Driver & Passenger Top:**  
Wrap the Velcro around to the side and press them to the carpet on the side of the seat.



**Step 7. DT&PT/Driver & Passenger Top:**  
Lastly, connect the sides of the seat cover to the carpet on the sides of the seat as shown.



**Step 8. DB&PB/Driver & Passenger Bottom:**  
Slide the seat covers on keeping the Velcro™ turned inside out so it doesn't stick while pulling it down.



**Step 9. DB&PB/Driver & Passenger Bottom:**  
Lift the drink holders out of the front of the Passenger seat and work the seat cover around it.



**Step 10. DB&PB/Driver & Passenger Bottom:**  
Tuck the top edge of the seat cover in.



**Step 11. DB&PB/Driver & Passenger Bottom:**  
Pull the cover back into position, again lining the seams of the seat cover to the seams on the seat, working the material inside the cover from forefinger to thumb.



**Step 12. DB&PB/Driver & Passenger Bottom:**  
Pull the top edge of the seat cover tight and press the hook Velcro™ to the carpet on the back edge of the seat.



**Step 13. DB&PB/Driver & Passenger Bottom:**  
Pull the bottom of the cover tight and press it the carpet under the seat as shown.



**Step 14. DB&PB/Driver & Passenger Bottom:**  
Lastly, slide the seatbelts thru the elastic sewn on the seat covers.