

2000-03 F-150 40/60 w/ Two Drink Console Installation



Step 1. Driver and Passenger Top/DT&PT:

All the parts of the seat cover are labeled inside the cover. Use the Seat Cover Piece Identification Chart to ID parts. Slide the seat covers on with the extending hook (sticky) Velcro™ to the front. Form the top of the seat cover to the seat. The seams of the seat covers should closely line up with the seams of your seat. Work the fabric seams inside the seat cover outward (from light grey to dark grey).



Step 2. Driver and Passenger Tops/DT&PT:

For extended cab and regular cab models only, tuck the fabric around the access lever behind the seat.



Step 3. Driver and Passenger Tops/DT&PT:

Tuck the hook Velcro™ into the seat and connect them to the loop (fuzzy) Velcro™ sewn inside the back edge. Do this by gently pulling on the Velcro™ from behind the seat with one hand and use the other hand in a smoothing action from the top to the bottom of the seat, connecting the Velcro™ at the bottom.



Step 4. Driver Bottom/DB:

Place the seat covers on with the long hook Velcro™ to the front. Again, the seams of the seat cover should closely line up with the seams of your seat. Work the seams of the fabric outward (from light grey to dark grey). Press the front hook Velcro™ to the carpet on the front of the seat under your knees, then route them under the seat and, pull tight, then press them to the carpet on the back edge of the seat bottom. Make sure to line up the front seam of the seat cover to the seam on your seat, avoiding pulling it too far down in front.



Step 5. Driver Bottom/DB:
Pull the inside edge back and press the hook Velcro™ to the carpet on the seat as shown.



Step 6. Driver Bottom/DB:
Slide the long outside edge hook Velcro™ down between the seat and the plastic. Loosening the screw behind the recline lever helps.



Step 7. Driver Bottom/DB:
For models with electric controls, lift the seat all the way up towards the ceiling. Carefully reach under the seat and feel for the Velcro™. Route it where shown, on top of the metal frame and press it to the carpet on the back of the seat. For models with manual controls, route it straight back inside the plastic cowl and press it to where you see the plastic wrapping around the back of the seat (left side of the photo) Move the seat to make sure the seat action is not impeded by the Velcro™.



Step 8. Driver Bottom/DB:
Lastly, pull the back edge of the seat cover back and mate the hook Velcro™ to the carpet, starting on one side moving to the other. Some repositioning of the Velcro™ may be needed to get the best fit. Gently slide the seat back and forth to make sure the Velcro™ are not impeding the seats actions. Re-route the Velcro™ as needed.



Step 9. Passenger Bottom/PB:
Remove the center seatbelt on the inside edge of the seat from its elastic restraint.



Step 10. Passenger Bottom/PB:
Place the seat cover on with the long hook Velcro™ to the front. Feed the seatbelts through the provided opening.



Step 11. Passenger Bottom/PB:

Pull the seat cover over the inside rear part of the seat below the console. Put the center seatbelt through the elastic restraint sewn to the seat cover. Press it to the hook Velcro™ sewn on the inside of the cover to the carpet on the back edge of the seat.



Step 12. Passenger Bottom/PB:

Place the seat covers on with the long hook fasteners to the front. Again, the seams of the seat cover should closely line up with the seams of your seat. Work the seams of the fabric outward (from light grey to dark grey). Press the long front hook Velcro™ to the carpet on the front of the seat under your knees, routing them under the seat and connect them to the carpet on the back edge of the seat. Slide the long outside edge hook Velcro™ between the seat and the plastic. Loosen screw same as in Step 6.



Step 13. Passenger Bottom/PB:

Pull the hook Velcro™ down through to the bottom of the plastic.



Step 14. Passenger Bottom/PB:

Pull the Velcro™ straight back inside the plastic cowling and press it to the carpet on the seat, routing it to the right or outside of the seat slide. Carefully slide the seat back and forth to make sure the seat's action is not impeded.



Step 15. Passenger Bottom/PB:

Connect the seat cover to the carpet behind the console. Pull the small piece of seat cover next to the seatbelt cut-out, between the console and passenger backrest and press it to the carpet on the back of the seat. Connect the remaining back edge of the seat cover to the carpet on the back of the seat bottom.



Step 16. Lid/L:

Place the lid cover on with the letter "L" inside the cover to the back. Slide the rear Velcro™ into the hinge using a sawing motion while moving the lid up and down, connect the Velcro™ as shown.



Step 17. Console/C:
With the console in the up position, slide the cover on and tuck the fabric behind the plastic on the right side.



Step 18. Console/C:
Tuck the fabric behind the plastic on the right side in front.



Step 19. Console/C:
Carefully tuck the top right side of the fabric behind the plastic using a thin feeler gauge or a butter knife without teeth.



Step 20. Console/C:
Pull the back edge of the console cover up to the hinge in back and press the hook Velcro™ on the back of the console cover and press it to the carpet under the hinge. Slide the rear Velcro™ thru the hinge. Work the edges of the fabric up to the lip where the fabric meets the plastic. Fold the Velcro™ into the box and note the areas where they will lay. Clean the areas with rubbing alcohol and a paper towel. Scrub hard and wipe it dry while it's still wet, don't let it air dry. Peel the plastic backing from the adhesive Velcro™ and press it to the plastic inside the box, pushing hard. Re-clean the areas if they aren't sticking.