

2002-03 Dodge Rear Bench Installation



Step 1. Bottom/B:

All the parts of the seat cover are labeled inside. Use the seat cover piece identification chart to ID parts. Tilt the seat bottom partway up, and slide the seat cover on with the letter "B" up. With the seat bottom up, pull the cover down by working each side a little at a time.



Step 2. Bottom/B:

With the seat bottom still up, work the seat cover fabric inside the seat cover to the center (pointer finger), lining up the seams of the seat cover to the seams of the seat, they should closely match. Lastly, pull down on the outside edge left and right side of the seat cover while using one hand in a smoothing action down the front and sides.



Step 3. Bottom/B:

Tuck the top side of the seat cover under the seat belts and tilt the seat up. Center the seat cover on the top side, making sure to have coverage on both left and right sides.



Step 4. Bottom/B:

Tilt the seat bottom partway up and use one hand in a smoothing action down the top side of the seat cover, while pulling with the other hand from the bottom. Work from one side to the other pressing the hook (sticky) Velcro™ to the fuzzy carpet on the seat.



Step 6. Top/T:

Center the seat cover left and right, move the nylon child restraints out of the way, and press the hook Velcro™ to the fuzzy carpet behind the seat. Note, some models do not have the fuzzy carpet.



Step 7. Top/T:

Press the hook Velcro™ to the fuzzy carpet in front of the center seatbelt.



Step 8. Top/T:

Tuck the seat cover in and press the left and right hook Velcro™ (pinky finger) to the carpet on the sides of the seat. Then, press the hook Velcro™ (thumb) sewn on the inside left and right to the carpet on the sides of the seat. Do this step with the seat bottom up.