

2004-09 Ford Ranger 60-40 Installation



Step 1. Driver & Passenger Top/DT&PT:
All the parts of the seat cover are labeled inside the cover. Use the seat cover part ID chart to identify the parts. Slide the cover on partway down with the extending hook Velcro™ to the front.



Step 2. Driver & Passenger Top/DT&PT:
Form the top of the seat cover to the top of the seat. Line up the seams of the seat cover to the seams of the seat, they should match closely.



Step 3. Driver & Passenger Top/DT&PT:
Manipulate the fabric inside the seat cover inward from thumb to forefinger around the top and sides of the seat.



Step 4. Driver & Passenger Top/DT&PT:
Tuck the hook Velcro™ into the seat and tip the seat forward.



Step 5. Driver & Passenger Top/DT&PT:
Use one hand in a smoothing action down the front of the cover while pulling on the Velcro™ from the back. Use the front hand to pin the Velcro™ to the seat and press the loop Velcro™ on the back of the cover to it.



Step 6. Driver & Passenger Bottom/DB&PB:
Place the seat cover on with the long hook Velcro™ to the front. Feed the seat belt through the provided opening.



Step 7. Driver & Passenger Bottom/DB&PB:
Pull the cover back into position, again lining up the seams, and tuck the fabric behind the plastic on the outside edge.



Step 8. Driver & Passenger Bottom/DB&PB:
Work the material inside the cover outward from thumb to forefinger around the front and sides of the seat.



Step 9. Driver & Passenger Bottom/DB&PB:
From behind the seat, pull the inside flap of material next to the console around to the back and press the hook Velcro™ onto the carpet on the seat.



Step 10. Driver & Passenger Bottom/DB&PB:
Slide the Velcro™ behind the plastic. Route it straight back along the outside edge of the seat, above the seat slide in back, then wrap it around to the back to the carpet on the seat. Carefully move the seat and make sure the Velcro™ isn't in the way of the slide.



Step 11. Driver & Passenger Bottom/DB&PB:
Tuck the back edge in.



Step 12. Driver & Passenger Bottom/DB&PB:
Route the long hook Velcro™ under the seat and press it to the seat carpet. Pull the back edge of the cover down and press it onto the seat carpet.



Step 13. Console/C:

With the console up, slide the cover on and tuck the fabric in around the hinge area.



Step 14. Console/C:

Slide the rear Velcro™ in next to the hinge and connect them to the long front Velcro™. Re-tighten the Velcro™ if needed to make sure they're really tight.



Step 15. Console/C:

Tightly connect these two side to side Velcro™ in front.



Step 16. Console/C:

Dry fit the remaining Velcro™ by laying them into the box. Clean those areas with rubbing alcohol by scrubbing hard then wiping dry while it's still wet.



Step 17. Lid/L:

With the console down, open all the Velcro™ and place the lid cover on with the letter "L" to the back.



Step 18. Lid/L:

Open the lid up and connect the Velcro™ underneath starting with the front to back ones first (or top to bottom as seen in the picture), then the side to side Velcro™. Re-tighten Velcro™ as needed for best fit.