

## 2004-09 Ford Ranger Bucket seat Installation



**Step 1. Driver & Passenger Top/DT&PT:**  
All the parts of the seat cover are labeled inside the cover. Use the seat cover part ID chart to identify the parts. Slide the cover on partway down with the extending hook Velcro™ to the front.



**Step 2. Driver & Passenger Top/DT&PT:**  
Form the top of the seat cover to the top of the seat. Line up the seams of the seat cover to the seams of the seat, they should match closely.



**Step 3. Driver & Passenger Top/DT&PT:**  
Manipulate the fabric inside the seat cover inward from thumb to forefinger around the top and sides of the seat.



**Step 4. Driver & Passenger Top/DT&PT:**  
Tuck the hook Velcro™ into the seat and tip the seat forward.



**Step 5. Driver & Passenger Top/DT&PT:**  
Use one hand in a smoothing action down the front of the cover while pulling on the Velcro™ from the back. Use the front hand to pin the Velcro™ to the seat and press the loop Velcro™ on the back of the cover to it.



**Step 6. Driver & Passenger Bottom/DB&PB:**  
Place the seat cover on with the long hook Velcro™ to the front. Feed the seat belt through the provided opening.



**Step 7. Driver & Passenger Bottom/DB&PB:**  
Pull the cover back into position, again lining up the seams, and tuck the fabric behind the plastic on the outside edge.



**Step 8. Driver & Passenger Bottom/DB&PB:**  
Work the material inside the cover outward from thumb to forefinger around the front and sides of the seat.



**Step 9. Driver & Passenger Bottom/DB&PB:**  
From behind the seat, pull the inside flap of material next to the console around to the back and press the hook Velcro™ onto the carpet on the seat.



**Step 10. Driver & Passenger Bottom/DB&PB:**  
Slide the Velcro™ behind the plastic. Route it straight back along the outside edge of the seat, above the seat slide in back, then wrap it around to the back to the carpet on the seat. Carefully move the seat and make sure the Velcro™ isn't in the way of the slide.



**Step 11. Driver & Passenger Bottom/DB&PB:**  
Tuck the back edge in.



**Step 12. Driver & Passenger Bottom/DB&PB:**  
Route the long hook Velcro™ under the seat and press it to the seat carpet. Pull the back edge of the cover down and press it onto the seat carpet.