

2005-2011 Dakota Crew Cab Rear Installation



Step 1. Driver & Passenger Seat:

Temporarily remove the headrests by lifting up the seat bottoms, the lift the headrest up all the way. Use gentle upward pressure on the headrest, insert a small Allen wrench into the holes in the plastic until it releases.



Step 2. Headrests/H:

All the parts of the seat cover are labeled inside. Use the Seat Cover Part ID Chart to identify parts. Slide the cover on with the extending hook Velcro™ to the front. Line up the seams of the cover to the seams of the headrest, they should match closely.



Step 3. Headrests/H:

Connect the Velcro™ as shown under the back edge.



Step 4. Driver & Passenger Top/DT&PT:

Driver side, pull the seat belt away from the seat and tuck the cover behind it.



Step 5. Driver & Passenger Top/DT&PT:

Tuck the seat cover under the plastic for the headrests.



Step 6. Driver & Passenger Top/DT&PT:

Line up the seams of the seat cover to the seams of the seat, they should match closely.



Step 7. Driver & Passenger Top/DT&PT:
Tuck the bottom corners of the seat cover around the front of the seat. Locate the long side hook Velcro™ on the left and right front corners.



Step 8. Driver & Passenger Top/DT&PT:
While kneeling outside the truck, use one hand to reach under the seat and feed the front Velcro™ around to the side of the seat and press it to the side of seat with the outside hand (left hand shown).



Step 9. Driver & Passenger Top/DT&PT:
Keep the hook Velcro™ pressed into the side of the seat with the left hand. Press the loop Velcro™ in the right hand, connecting the two.



Step 10. Driver & Passenger Bottom/DB&PB:
Lift the seat bottoms up. Slide the covers on with the lettering inside the covers "DB & PB" to the top. Form the seat covers to the seat, again lining up the seams of the seat cover to the seams of the seat, they should match closely. Work the seat cover fabric on the inside from thumb to forefinger around the corners.



Step 11. Driver & Passenger Bottom/DB&PB:
Pull the back edge down and press it to the caret fuzz as shown.



Step 12. Driver & Passenger Bottom/DB&PB:
Lastly, pull the bottom edge down and press it to the carpet fuzz on the underside of the seat.