

2009-2010 F-150 Super Cab 60-40 Rear Installation



Step 1. Headrests/H:

All the parts of the seat cover are labeled inside. Use the seat cover piece identification chart to ID parts. Slide the headrest covers on with the extending hook (sticky) Velcro™ to the front. 2009 has smaller headrests.



Step 2. Headrests/H:

Tuck the hook Velcro™ under the headrest and connect them to the loop Velcro™ sewn inside the back edge.



Step 3. Top/T:

Tuck the seat cover behind the center seat belt, and open the Velcro™ for the headrests



Step 4. Top/T:

Tuck the seat cover under the plastic for the headrests and mate the Velcro™ behind with a small gap.



Step 5. Top/T:

Jam the seat cover fabric between the seat and back wall. Gently using a butter knife will help like a shoe horn to get it in behind the seat



Step 6. Top/T:

Pull the left and right top corners over the top of the seat and form the cover to it, lining up the seams of the seat cover to the seams of the seat, they should closely match.



Step 7. Top/T:
Tuck the seat cover between the seat and the four child restraints.



Step 8. Top/T:
Tuck the long front right and left hook Velcro™ into the seat, around the inside of the outside child restraint.



Step 9. Top/T:
Using two hands, route the long left and right hook Velcro™ and press them to the loop Velcro™ sewn on the side of the seat covers.



Step 10. Driver Bottom/DB:
Remove the two female seat belt ends from the factory restraint.



Step 11. Driver & Passenger Bottom/DB& PB:
Slide the covers on with the seat cover turned up and the hook Velcro™ away from the seat bottom.



Step 12. Driver & Passenger Bottom/DB& PB:
Tuck the cover behind the plastic on the sides.



Step 13. Driver & Passenger Bottom/DB& PB:
press the top side Velcro's first as shown.



Step 14. Driver & Passenger Bottom/DB& PB:
Lastly, press the bottom side Velcro™ as shown.