

## No2014-2019 Chevy/GMC 40-20-40 w/ Non-opening Middle Bottom Installation



### Step 1. Headrests/H:

All the parts of the seat cover are labeled inside. Use the seat cover part ID chart to ID parts. Slide the headrest covers on with the extending Velcro™ to the front. Recline the backrests and temporarily remove the headrests by depressing the push button release on each post simultaneously while gently lifting up.

**Install can be seen on our YouTube channel. The Link is:** <https://youtu.be/GxORqCxcvI8>



### Step 2. Headrests/H:

Tuck the Velcro™ under the back edge and press them together. Recline the backrests and temporarily remove the headrests by depressing the push button release on the one side, and lift the headrest all the way up. Then, push a small Allen wrench or heavy wire into the hole in the plastic on the other post (Right hand) while gently lifting up until the headrest releases. If you are having trouble removing them, call 877-485-3001.



### Step 3. Driver & Passenger seat preparation.

Feel under the back edge of the seat on each side for the elastic straps. They are connected to support wires under the seat with the plastic clips shown in the picture. They're fairly difficult to remove. Pry the plastic clip open while pushing it forward. I used my fingers to pry it open, but you may opt for a tool of some sort to pry it open.



### Step 4. Driver & Passenger Bottom/DB&PB:

Place the seat cover on with the extending hook Velcro™ to the front. Tuck the seat cover behind the plastic cowl on the outside edge. For electric seat controls, lift the seat all the way up and move it forward. Line up the seams of the seat cover to the seams on the seat around the outside edge, they should match closely.



**Step 5. Driver & Passenger Bottom/DB&PB:**

Work the fabric from the seam inside the seat cover outwards, or from forefinger to thumb.



**Step 6. Driver & Passenger Bottom/DB&PB:**

Tuck the back edge in. You will need to find something or someone to hold the back flap up behind the seat in order to install the seat covers. Be very careful, the bottom of the flap has a very sharp edge on it. Use caution when reaching under the seat. All the metal edge are sharp as a knife, and all the moving parts have grease on them. Check your hands every time they come from under the seat.



**Step 7. Driver & Passenger Bottom/DB&PB:**

Fold the all of the front edge and outside edge Velcro™ in half lengthwise with the hook facing in. This will stiffen Velcro™ and make it easier to route under the seat. Look under the front of the seat and poke the Velcro™ straight thru to the back.



**Step 8. Driver & Passenger Bottom/DB&PB:**

Likewise with the left and right side Velcro™, fold them in half lengthwise. Push the outside edge Velcro™ straight down where shown.



**Step 9. Driver & Passenger Bottom/DB&PB:**

Feel for the outside edge Velcro™ in the gap shown, pull it back and press it to the loop Velcro™ sewn on the back edge.



**Step 10. Driver & Passenger Bottom/DB&PB:**

Likewise for the inside edge Velcro™. Push it down thru the gap shown and route it to the back edge and press it to the rear loop Velcro™. Note, some repositioning of the Velcro™ may be needed to accommodate the Velcro™ of the seat cover top.



**Step 11. Driver & Passenger Bottom/DB&PB:**

Snap the plastic clip over the metal support wire under the back edge of the seat where shown, and press the hook Velcro™ to the loop Velcro™ sewn on the back edge. This will keep the seat cover from shifting around. Carefully trim the excess Velcro™



**Step 12. Driver & Passenger Top/DT&PT:**

Slide the seat cover on with the extending hook Velcro™ to the front as shown. Again, line up the seams of the seat cover to the seams of the seat, they should match closely.



**Step 13. Driver & Passenger Top/DT&PT:**  
Tuck the seat cover under the plastic for the headrests, starting on the push button side.



**Step 14. Driver & Passenger Top/DT&PT:**  
Tuck the front edge of the seat cover in.



**Step 15. Driver & Passenger Top/DT&PT:**  
While pulling on the seat cover from behind, right where the Velcro™ is sewn on, slide one hand down the front side of the seat in a smoothing action taking up the slack. Make sure you're backrest are positioned slightly forward from normal. When the seat cover is fully installed, recline the backrests to the normal positions, it'll help tighten the front side even more.



**Step 16. Driver & Passenger Top/DT&PT:**  
Route each of the long hook Velcro™ under the back edge of the seat and around the outside support wire, the same area the plastic clip connected to. Take up the slack again as in Step 15, then reach under the seat and take up the slack in the Velcro™ by pulling it forward and connect as shown in Step 17. It's helpful to press the seat cover with one hand to the seat while taking up the slack in the Velcro™ with the other hand.



**Step 17. Driver & Passenger Top/DT&PT:**  
Press the Velcro™ together, trim the excess. Next re-connect the plastic clips to the metal bar. You'll see the Velcro™ is where it needs to connect, which is what you want. Hold the clip in position with one hand, then pull back on the elastic with the other hand and it'll clip back on.



**Step 18. Driver & Passenger Top/DT&PT:**  
Pull the backside down and press the hook Velcro™ onto the carpet on the backside of the seat.



**Step 19. Console/C:**  
Carefully open the bottom of the cover and place the cover on as shown.



**Step 20. Console/C:**  
Fold the console down, tuck the cover in on the front and on both left and right sides. Pull the back edge up and connect the side Velcro™ as shown



**Step 21. Console/C:**

Open the console lid and pull the material up to the back edge. Fold the Velcro™ inside the plastic box of the console and note the areas they will lay. Clean the areas with rubbing alcohol by scrubbing the area hard, and wiping it dry while it's still wet. This will remove all the residue and allow proper adhesion. If they don't stick, re-clean the area until they do. Extra adhesive Velcro™ is provided.



**Step 22. Console/C:**

Press the Velcro™ hard onto the plastic where shown.



**Step 23. Lid/L:**

Carefully disconnect the Velcro™ on the lid cover. They will stick when you don't want em to, so use patience as your guide when installing the lid cover. Work on it from behind the console. With the Velcro™ disconnected, lay the cover on with the console in the down position. Hold the cover on the lid with one hand and open it with the other hand. Lean into the cover with your body to hold it while you connect the Velcro™ on the underside. Re-hook and tighten the Velcro™ until the cover is in place and fits snug.



**Step 24. Middle Bottom/MB:**

Place the seat cover on with the extending hook Velcro™ to the front. Again, line up the seams of the seat cover to the seams on the seat as in Step 4. Tuck the back edge in a little just to hold the cover in place.



**Step 25. Middle Bottom/MB:**

Fold the Velcro™ in half lengthwise with the sticky part inward. This will stiffen the Velcro™ and keep it from sticking to other parts of the seat.



**Step 26. Middle Bottom/MB:**

Slide the driver and passenger seat forward all the way. Feel for the Velcro™ behind the metal bar, and push it to the back, keeping it up near the seat, then feel for it with the other hand behind the seat.



**Step 27. Middle Bottom/MB:**

Pull the Velcro tight and press it to the carpet on the seat.



**Step 28. Middle Bottom/MB:**

Pull the left and right side Velcro™ back between the seats. Fold it in half lengthwise and slide it in front of the metal at an angle to the back.



**Step 29. Middle Bottom/MB:**

Pull the side Velcro™ tight and press it to the carpet on the back edge of the seat.



**Step 30. Middle Bottom/MB:**

With all the Velcro™ connected to the back edge, pull the back edge tight and press it to the carpet.