

2018 Jeep Wrangler JL Buckets Installation



Step 1. Prep:

Lift your seat up as much as possible. This will give you a little extra room to work with.



Step 2. Prep:

Take your headrests off by pushing both buttons on the peg plastics and pulling the headrest up.



Step 3. Prep:

Reach under your seats from behind. You'll feel 2 loops of elastic looped over some hooks. Pull the elastics off the hooks and lift your back panel up.



Step 4. Headrests/H:

All our pieces are labeled on the inside of the piece. Each having a letter representing the piece. Find the H (Headrests) and slide them over your headrests with the extending Velcro on the front. Wrap the flap under the headrest and connect it to the Velcro on the underside of the back.



Step 5. Driver Bottoms/DB:
Before putting the cover on, disconnect any Velcro. Take the 2 buckles and save them for later. There is a cut out on the driver bottom for the lumbar knob. Fit the cover under one side of the knob then pull it over the rest. It's going to be tight so the material will suck in behind the knob.



Step 6. Driver & Passenger Bottoms/DB&PB:
Place the rest of the cover over the seat. Make sure to match the seam of the seat cover to the outside seam of the seat.



Step 7. Driver & Passenger Bottoms/DB&PB:
Tuck the cover behind the plastic on the outside edge of the seat.



Step 8. Driver & Passenger Bottoms/DB&PB:
Take the top flap and tuck it in-between the seat bottom and top.



Step 9. Driver & Passenger Bottoms/DB&PB:
Reach behind the seat and pull the cover down tight. This will help form the cover on the rest of the seat.



Step 10. Driver & Passenger Bottoms/DB&PB:
Take the long Velcro on the front of the cover and fold them in half long ways. This will stiffen them up and make it easier to feed under the seat.



Step 11. Driver & Passenger Bottoms/DB&PB:
Feed the Velcro under the seat and toward the back of the seat. Make sure to go over any loose wires or low hanging bars. Anything strapped tight to the seat is ok to go under.



Step 12. Driver & Passenger Bottoms/DB&PB:
Pull the seat cover tight and connect the front Velcro to the flap.



Step 13. Driver & Passenger Bottoms/DB&PB:
Take the Velcro on the door side of the seat and feed it under the seat between the seat and rails.



Step 14. Driver & Passenger Bottoms/DB&PB:
Then grab the Velcro, pull tight and connect it to the seat cover.



Step 15. Driver & Passenger Bottoms/DB&PB:
Repeat the same process for the Velcro that is on the inside side of the cover.



Step 16. Driver & Passenger Bottoms/DB&PB:
Take the buckles from earlier and clip them onto the metal bars under the seat. Hook them around the bars toward the center of the seat. Then pull them tight and connect them to the flap.



Step 17. Driver & Passenger Bottoms/DB&PB:

Cut off any excess Velcro. Be careful not to cut any wires or the cover itself.



Step 18. Driver & Passenger Tops/DT&PT:

Detach any Velcro and save the buckles for later. Take the top covers and pull them over the backrests. These pieces are labeled DT and PT but if you aren't sure, the driver top has our logo on it. Pull the covers down all the way making sure to match the seats of the cover with the seams of the seat.



Step 19. Driver & Passenger Tops/DT&PT:

Poke the headrest plastics through the holes at the top of the cover.

***Important:** Make sure you poke them through starting on the push button side. If you go the other way, you risk braking the plastic.




Step 20. Driver & Passenger Tops/DT&PT:

Take the front flap and tuck it in-between the backrest and bottom. Then go behind the seat and pull it tight.



Step 21. Driver & Passenger Tops/DT&PT:

Take the buckles and hook them to the metal bars under the seat, toward the edges of the seat.



Step 22. Driver & Passenger Tops/DT&PT:

Take the buckle Velcro and connect it to the loop Velcro on the flap you pulled through the seat.



Step 23. Driver & Passenger Tops/DT&PT:
Take the elastics from step 3 and reconnect them under the seat. Now take the back of the cover and pull it down tight and connect it to the fuzz on your seat.



Step 24. Lid/L:
Disconnect the Velcro and set it over the lid with the "L" at the back of the lid.



Step 25. Lid/L:
Open just the top section of the lid and connect the Velcro. Make sure the horizontal Velcro are loose enough to fit into the crevasses. If they are too tight, your lid will not shut. The vertical Velcro can be tightly fastened.



Congratulations!
Your cover is now installed! If you need any more install help, please reference or install video at:
<https://youtu.be/LnwL7Lgv4IE>