

2019-2024 Chevy/GMC 40/20/40 with Opening Consoles



Step 1. H: Headrests

The installation can be viewed on our YouTube channel: <https://youtu.be/rQ2nVcHn1s>
Please note, the headrests are difficult to remove, but not impossible. Using an Allen wrench or similar tool, push the fabric down exposing the small ring being pointed at. Hook your Allen wrench into the ring and push back. When the post releases, pry your hand under the headrest holding gentle upward pressure keeping the post from going back into the seat. While holding the released post up, release the other post using the same method, evenly sliding the headrest out of the seat.



Step 2. H: Headrests

All the parts of your seat cover are labeled on the inside right of each part. Use the seat cover Part ID chart to ID parts. Slide the headrest cover on with the extending hook Velcro™ to the front. Tuck the fabric under the button on the side. Line up the seams of the cover to the seams on the headrest, they should closely match. Connect the front hook Velcro™ to the loop Velcro™ sewn inside the back edge.



Step 3. MB: Middle Bottom

Place the cover on as shown, tucking in the back edge and aligning the cover on left and right.



Step 4. MB: Middle Bottom

Lift the seat bottom up and connect the hook Velcro™ to the fuzzy carpet under the seat as shown



Step 5. C: Console

Carefully disconnect the Velcro™. Slide the cover on as shown, holding the seatbelt out of the way.



Step 6. C: Console

Tuck the fabric under the plastic for the seat belt.



Step 7. C: Console

Next, tuck the fabric behind the plastic cowlings on left and right as shown.



Step 8. C: Console

Connect the Velcro™ behind the seatbelt as shown.



Step 9. C: Console

Fold the Velcro into the console cavity and note where they will connect. Prepare the surface for the adhesive Velcro™ with rubbing alcohol and paper towel. Wet the towel and scrub the areas hard, wiping them clean while it's still wet. This removes any residue from the cleaning. Next, peel off the backing on the adhesive hook Velcro still connected to the loop Velcro on the cover, pressing it onto the plastic hard. If the Velcro doesn't stick, re-clean the area with soapy water, then rubbing alcohol. Extra adhesive Velcro™ is provided.



Step 10. L: Lid

Carefully disconnect the Velcro, and place the cover on with the Velcro™ splayed out as shown. If possible, install the cover from behind. Use your knee's to hold the back of the cover in place and pull the front edge on.



Step 11. L: Lid

Use one hand to hold the cover in place, then lift the console lid up. Connect the front to back, or top to bottom Velcro™ first, then the side Velcro™. Once in place, re-tighten each Velcro™. Do this by pulling on the connected to gain some slack. Then disconnect the Velcro™, holding onto the ends of each Velcro™, pulling hard and reconnecting them.



Step 12. Seat Preparation

View from behind the seat. First, disconnect the two plastic clips from under the seat that hold the carpeted flap to the backside of the seat. Note the areas where you disconnected them from, and avoid routing Velcro™ over the areas.



Step 13. DB/PB: Driver & Passenger Bottom

Each seat cover bottom is marked on the inside back right edge "DB or PB" for driver and passenger bottoms respectively. Carefully disconnect all the Velcro™, and set aside the two "safety buckles" and set aside. For electric controlled seats, lift them all the way up, clearing a path for the Velcro™ to run under the seat, above all the metal framework. Sliding the seats forward will give you room to work from behind the seat. Place the cover on as shown, lining up the seams of the seat cover to the seams on your seat, they should match closely. Carefully tuck the cover behind the plastic cowling, and tuck the back edge into the seat.



Step 14. DB/PB: Driver & Passenger Bottom

View from behind the driver seat. Grab onto the back edge of the cover and pull. Use one hand in a smoothing action from front to back on the cover to gain slack and tighten the cover to the front of the seat.



Step 15. DB/PB: Driver & Passenger Bottom

Fold the long front hook Velcro™ lengthwise with the hook facing in. This will stiffen the Velcro up like a ruler and make it easy to route the Velcro™ to the back edge. Route the Velcro™ keeping it up directly under the seat avoiding wiring, electric motors, and the metal framework. Using the smoothing method in Step 14, tighten the cover, and connect the long front hook Velcro™ to the loop Velcro™ sewn on the back edge, avoiding the areas the clip connects to shown in Step 12.



Step 16. DB/PB: Driver & Passenger Bottom

View of the outside edge of the driver seat bottom. Push the seat away from the plastic cowling as shown, noting the gap to feed the side Velcro™ thru. Same as Step 15, fold the Velcro™ in half lengthwise to stiffen it up making it easier to route to the back edge.



Step 17. DB/PB: Driver & Passenger Bottom

Lift up the middle seat, and route the inside edge Velcro™ under the seat, avoiding seat mechanisms and angle it to the back of the seat.



Step 18. DB/PB: Driver & Passenger Bottom

Working from behind the seat, locate the side Velcro™, routing them making sure to avoid the seat mechanisms and the clip locations from step 12.



Step 19. DB/PB: Driver & Passenger Bottom

While gently pulling on the side Velcro™, use one hand in a smoothing action along the side of the seat from front to back taking up any slack in the cover, then connect the hook Velcro™ to the loop Velcro™ sewn on the back edge. Do the same for both sides.



Step 20. DB/PB: Driver & Passenger Bottom

Lastly, connect the two “safety buckles” under the back edge of the seat to the same metal bar the clips fastened to in Step 12, avoiding the areas for the clips. Connect the safety buckles to the loop Velcro™ sewn on the back edge, trim the excess. This step keeps your seat bottom anchored and keeps it from sling around.



Step 21. DT/PT: Driver & Passenger Top

Provisions are made for the side impact airbags. It is critical to get the covers on the correct side.

The covers are marked on the inside front right "DT & PT" for Driver & Passenger Tops. Also note, the Driver Top has our Headwaters Seat Cover label on the backside. Disconnect the plastic buckles with hook Velcro™ and set them aside. Slide the covers on with "DT & PT" to the front.



Step 22. DT/PT: Driver & Passenger Top

Center the cover on left and right as you continue to pull it into place. Next, carefully tuck the fabric under the plastic for the headrests. Form the top of the seat cover to the top of the seat, again lining up the seams of the seat cover to the seams of your seat, they should match closely. Tuck in the front edge of the seat cover, and again using one hand in a smoothing action from top to bottom on the front side of the seat cover while pulling on the fabric behind the seat, taking up slack in the cover.



Step 23. DT/PT: Driver & Passenger Top

Pull the cover down into place.



Step 24. DT/PT: Driver & Passenger Top

Connect the plastic hooks under the seat to the same metal bar as in Step 12, lining them up with the loop Velcro™ sewn to the seat cover.



Step 25. DT/PT: Driver & Passenger Top

Pull the cover down hard, connecting the buckle Velcro™ to the loop Velcro™ sewn to the cover.



Step 26. DT/PT: Driver & Passenger Top

Reconnect the factory plastic clips from Step 12 under the seat. You may have to adjust previously connected Velcro slightly to expose the clip area.



Step 27. DT/PT: Driver & Passenger Top

Lastly, pull down and press the hook Velcro™ sewn inside the cover to the fuzzy carpet on the seat as shown.



Congratulations!

Your properly installed seat cover should look like it's painted on, and stay in place until you remove them.