

1992-96 Jeep Wrangler Rear Bench Installation



Step 1. Seat Preparation:
Fold the seat forward and remove the pins on left and right as shown. Slide the whole seat to the right and remove it. Place it on a table for an easier installation.



Step 2. Top/T:
The Top is labeled "T" on the inside front right corner. Slide the seat cover with the extending hook Velcro™ to the front.



Step 3. Top/T:
Work the fabric inside the covers around the top corners from pointer finger to thumb. Line up the seams of the seat cover to the seams on your seat, they should match closely.



Step 4. Top/T:
Tuck the Velcro™ into the seat. Use one hand in a smoothing action down the front of the seat cover while gently pulling on the Velcro™ from the backside with the other hand. Use the front hand to pin the Velcro™ to the seat, then press the Velcro™ together. Work your way across from one side to the other.



Step 5. Bottom/B:

Slide the cover on with the Velcro™ sewn inside to the bottom side of the seat. Turning it inside out will help it from catching while you're pulling it down.



Step 6. Bottom/B:

Locate the two openings for the seat bracket and line them up.



Step 7. Bottom/B:

Same as Step 7, work the fabric around the corners and line up the seams.



Step 8. Bottom/B:

Tuck the top side Velcro™ into the seat, pull them tight, and then press them to the carpet on the underside of the seat. Lastly, pull the seat cover bottom side down and press the Velcro™ to the carpet on the seat bottom. re-install the seat and you're done.