

## 2002-08 Jeep Liberty 40-60 Rear Installation



### Step 1.

Fold the driver's backrest forward and temporarily remove the bolt for the center shoulder seat belt with a # 15 Metric socket.



### Step 2. Headrests/H:

All the parts of the seat cover are labeled on the inside right of each part. Use the seat cover part ID chart to ID parts. Slide the headrest covers on while they're still on the seat. Note: The sides will be compressed until the cover is pulled all the way down.



### Step 3. Headrest/H:

Temporarily remove the headrests by gently lifting up and depressing the push button release on the plastic. Align the seams of the headrest cover to the seams of the headrest, they should closely match. Tuck the hook Velcro™ under the back edge and connect it to the loop Velcro™ sewn inside.



### Step 4. Driver and passenger Bottom/DB&PB:

Place the cover on with the long hook Velcro™ to the front. As in Step 2, align the seams of the seat cover to the seams of the seat, they should match closely.



### Step 5. Driver and Passenger Bottom/DB&PB:

Route the side hook Velcro™ at an angle to the back edge of the seat bottom and press them onto the carpet on the back edge of the seat. Route the long hook Velcro™ under the front of the seat and press them onto the carpet on the back edge of the seat.



### Step 6. Driver and Passenger Bottom/DB&PB:

Temporarily disconnect the carpeted flap behind the seat.





**Step 7. Driver and Passenger Top/DT&PT:**

Lastly, tuck in the back edge of the seat cover, making sure to keep the loop Velcro™ covering the hook Velcro™. This will enable you to poke it thru to the back. Once pulled thru, fold the seat flat, remove the loop Velcro™, pull back hard and press the hook Velcro™ onto the carpet on the back edge of the seat bottom.



**Step 8. Passenger Top/PT:**

Pull the seat cover on with the abbreviation PT to the front side of the seat. Feed the disconnected seat belt thru the provided opening in the top of the PT. Driver seat, pull the cover on with the abbreviation DT to the front.



**Step 9. Driver and Passenger Top/DT&PT:**

Tuck the fabric under the plastic for the headrests.



**Step 10. Driver and Passenger Top/DT&PT:**

Make sure the loop Velcro™ is covering the hook Velcro™, it'll help you tuck it thru to the back.



**Step 11. Driver and Passenger Top/DT&PT:**

Tuck the front edge into the seat and fold it forward.



**Step 12. Driver and Passenger Top/DT&PT:**

Remove the loop Velcro™ covering the hook Velcro™, pull hard and press it to the carpet on the seat.



**Step 13. Driver and Passenger Top/DT&PT:**  
Fold the seat flat and pull the inside Velcro™ around to the back and press it to the carpet on the seat back.



**Step 14. Driver and Passenger Top/DT&PT:**  
Pull the hook Velcro™ in front of the seat belt tight and press them to the carpet on the seat back.



**Step 15. Driver and Passenger Top/DT&PT:**  
Press the back edge of the seat cover to the carpet on the seat back



**Step 16. Driver and Passenger Top/DT&PT:**  
Reconnect the carpeted flap to the loop Velcro™ sewn on the outside of the seat cover.