

2011-16 F-250 & 350 Super Cab Rear 40-60 bottom/Bench Backrest Installation

The parts of your seat cover are labeled inside. Refer to the "Seat Cover Piece Identification Chart" to identify the different parts of the seat cover.



Step 1. Top/T:

Carefully open the Velcro™ on the top of the seat cover, and place it on the seat with the cut-out for the seatbelt and the openings for the headrests to the top of the seat.



Step 2. Top:

Connect the Velcro™ behind the headrests posts, and tuck the top of the seat cover way down behind the seat and back of the cab, aligning the headrest holes along the top of the seat.



Step 3. Top:

Pull the seat cover around the left and right side, lining up the seams of the seat cover with the seams of your seat, they should closely match.



Step 4. Top:

Tuck the two left and right front hook Velcro™ into the seat and mate them to the corresponding loop (fuzzy) Velcro™ sewn inside the sides of the seat cover.



Step 4. Passenger Bottom/PB:

Remove the seatbelts from their elastic restraints in the middle of the seat.



Step 5. Top:

Driver and Passenger Bottom/DB & PB:

With the seat in the up position, slide the covers on with the extending hook Velcro™ to the top side of the seat. Tuck the fabric behind the latch and the plastic on the outside edges. With the seat partway up use one hand in a smoothing action from front to back to remove slack from the seat cover. **Models without carpet** under the seat, mate the hook Velcro™ to the loop Velcro™ on the underside of the seat.

For models with carpet, mate all the hook Velcro™ to the carpet under the seat starting with the extending top hook Velcro™.