

2001-2004 Tacoma Extended Cab rear Installation



Step 1. Driver & Passenger Bottom/DB&PB:
All the parts of the seat cover are labeled inside. Use the seat cover part ID chart to ID parts. Slide the covers on with the extending hook Velcro™ to the top.



Step 2. Driver & Passenger Bottom/DB&PB:
Tuck the Velcro™ into the seat and fold the seat up.



Step 3. Driver & Passenger Bottom/DB&PB:
Flip the seat up, pull the hook Velcro™ through and pull them tight, then connect the Velcro™ as shown.



Step 4. Top/T:
It isn't necessary to remove backrest to install the seat covers. Damage could be done to the clips holding the plastic cowl and be expensive to repair. It may be removed by carefully prying the plastic cowl from under the rear window off, then prying the plastic from the underside of the backrest, then removing the #10 Metric bolts on top and bottom.
To install it without removing it from the truck:
Pull the top corner of the seat away from the back wall and slide the long hook Velcro™ around the top corners on right and left, then continue sliding it straight down to the bottom side of the seat. Use the Velcro™ to pull the seat cover around the top corners and behind the seat.



Step 5. Top/T:

View from under the seat. Pull the hook Velcro™ thru to the bottom side of the seat, then pull the left and right sides of the seat cover around the bottom corners.



Step 6. Top/T:

Connect the Velcro™ at the bottom of the seat by pinning the hook Velcro™ under the seat with one hand, then pull the around the bottom corner of the seat, pressing the Velcro™ together.



Step 7. Top/T:

Tuck the top edge of the seat cover in between the seat and the back wall by carefully using a flat screw driver to push the material in, then press it down behind the seat by levering the screwdriver up, thus pushing the material behind the seat.