

2014-2021 Tundra Crewmax Rear Installation



Step 1. Headrests/H:

All the parts of the seat cover are labeled inside the cover. Use the seat cover Part ID Chart to ID parts. Slide the headrest covers on with the long hook (sticky) Velcro™ to the front while the headrests are still on the seat.



Step 2. Headrests/H:

Line up the seams of the seat cover to the seams of the headrest, they should closely match. Tuck the front hook Velcro™ under the back edge and press the Velcro™ together.



Step 3. Driver & Passenger Bottoms/DB&PB:

Lift the seat bottoms up partway and slide the seat cover on with the cut-out for the seat release to the outside as shown. Turn the Velcro™ on the bottom of the seat inside out to keep it from sticking while you pull it down into position.



Step 4. Driver & Passenger Bottoms/DB&PB:

Fold the seat bottoms down and push the top side of the seat cover in between the seats. As in Step 2, line up the seams of the seat cover to the seams on the seat, they should closely match.



Step 5. Driver & Passenger Bottoms/DB&PB:

While pulling on the back edge of the seat cover, use one hand in a smoothing action down the top side of the seat smoothing and tightening the seat cover. Lastly, press the hook Velcro™ sewn on the underside of the seat cover to the fuzzy carpet under the seat.



Step 6. Driver Bottoms/DB:

Temporarily remove the seat belt that is located next to the passenger seat from the elastic (not shown). Tuck the seat cover around the center seat belt and down to the bottom side.



Step 7. Driver Bottoms/DB:

Lift the driver seat bottom up and pull the seat cover down inside the opening for the seat belt as shown and press the Velcro™ to the carpet fuzz under the seat bottom. Follow Steps 4 & 5 to finish installing the driver seat bottom.



Step 8. Driver & Passenger Top/DT&PT:

Lift the seat bottoms up to pull the top of the seat away from the rear window. place the seat cover on top of the seat, feed the nylon loop for the child restraint thru the seat cover, then tuck the seat cover behind the plastic for the headrests. Form the top of the seat cover to the seat.



Step 9. Driver & Passenger Top/DT&PT:
Carefully disconnect the side Velcro™ on each side and tuck the seat cover in on left and right as shown.



Step 10. Driver & Passenger Top/DT&PT:
View from under the passenger seat showing the Passenger Top "PT" under the outside edge. Carefully open the bottom left and right sides of the seat cover by disconnecting the Velcro™. Tuck the seat cover and front Velcro™ in with the child restraint exposed as shown.



Step 11. Driver & Passenger Top/DT&PT:
View of the Passenger Top outside edge near the bottom, just above the plastic cowling. Lift the seat bottoms up. Connect the inside edge Velcro™ where the backrests meet in the center by laying on your back on the floor facing up. Route the bottom edge Velcro™ around to the side of the seat, pull the side of the seat cover tight with the other hand and hold it in place, then connect the hook Velcro™ to the loop Velcro™ sewn inside the side of the seat cover. Connect the outside edge Velcro™ by kneeling outside and reaching up to connect the Velcro™.



Step 12. Driver Top/DT:
Follow Steps 8-10 to this point. Carefully open the Velcro™ on the top of the seat cover where the center seatbelt is. Slide the seat cover between the seat belt and the seat as shown. Tuck the seat cover fabric under the plastic for the center seatbelt. Pull the armrest down and open the seat cover, then tuck the seat cover behind the armrest and push it into the cavity of the armrest.



Step 13. Driver Top/DT:
Connect the Velcro™ and tuck the seat cover behind the plastic and tuck the seat cover behind the top of the seat.



Step 14. Driver Top/DT:
The picture is showing the bottom edge of the seat in the center seatbelt area. Route the hook Velcro™ on each side of the seatbelt around the metal bar and connect it to the loop Velcro™ sewn inside the seat cover. Tighten as needed for best fit.



Step 15. Driver Top/DT:
Place the seatbelt thru the elastic sewn on the seat cover.



Step 16. Driver Top/DT:
Tuck the seat cover under the armrest.



Step 17. Driver Top/DT:

Fold the armrest down and pull the Velcro™ and material up behind the armrest



Step 18. Driver Top/DT:

While holding the front edge hook Velcro™ in place, press the back of the armrest cavity loop Velcro™ onto the front hook Velcro™.



Step 19. Armrest/A:

With the armrest partway folded down, slide the cover on with the opening for the drink holders to the top.



Step 20. Armrest/A:

Once the cover is lined up left and right and pulled down onto position, tuck the front hook Velcro™ in and fold the armrest down. Connect the Velcro™ in back.